

Battery Status Report

SOH Blitz Test

Vehicle Information

/Skoda/Enyaq 2021 >, Elroq 2025 >
Odometer Reading: 8319km

VIN:
Rated Voltage: 396 V
Rated Capacity: 156 Ah

Test Time: 2026-10-13 14:34:15
Testing Organization: Automobilių patikra prieš
pirkimą
Customer:
S/N: V6DGS9V01123
Version: V14.10



Scan to download
PDF



Battery Status

Pack Information

A

Battery Health Status

SOH*:100 %

SOC:73 %

A

Static Temperature Consistency

Battery Temperature:10.9 °C

Max Temperature Delta:0.8 °C

A

Static Voltage Consistency

Battery Voltage:425.00 V

Max Voltage Delta:7 mV

Energy

62 kWh | 62 kWh

New vehicle's range on a full charge (WLTP)

408 km | 408 km

*: Based on the BMS data or related data of the vehicle manufacturer. Autel provides no guarantee regarding the actual SOH or physical condition of the battery.

Battery DTCs

No fault codes detected

Test Parameters

Module Voltage Information									
Maximum Module Voltage:		47.23 V				Minimum Module Voltage:		47.18 V	
Average Module Voltage:		47.21 V				Module Voltage Delta:		0.04 V	
Standard Module Voltage Delta:		0.01 V							
Maximum Cell Voltage:		3.937 V				Minimum Cell Voltage:		3.93 V	
Average Cell Voltage:		3.934 V				Cell Voltage Delta:		7 mV	
Standard Cell Voltage Delta:		1 mV							
Low High Warning Not OK									
Module		Cell							
		1	2	3	4	5	6	7	8
M1 (#1- #12)	47.22 V	3.935 V	3.935 V	3.934 V	3.934 V	3.935 V	3.935 V	3.935 V	3.936 V
		3.934 V	3.935 V	3.934 V	3.937 V				
M2 (#13- #24)	47.23 V	3.936 V	3.935 V	3.935 V	3.935 V	3.935 V	3.936 V	3.937 V	3.936 V
		3.936 V	3.934 V	3.935 V	3.935 V				
M3 (#25- #36)	47.19 V	3.933 V	3.932 V	3.933 V	3.933 V	3.934 V	3.932 V	3.931 V	3.933 V
		3.933 V	3.933 V	3.933 V	3.933 V				
M4 (#37- #48)	47.18 V	3.931 V	3.934 V	3.932 V	3.933 V	3.932 V	3.931 V	3.93 V	3.931 V
		3.931 V	3.934 V	3.933 V	3.933 V				
M5 (#49- #60)	47.22 V	3.935 V	3.935 V	3.934 V	3.935 V	3.936 V	3.935 V	3.933 V	3.934 V
		3.936 V	3.935 V	3.935 V	3.936 V				
M6 (#61- #72)	47.2 V	3.934 V	3.931 V	3.933 V	3.932 V	3.933 V	3.935 V	3.933 V	3.933 V
		3.932 V	3.932 V	3.933 V	3.936 V				
M7 (#73- #84)	47.2 V	3.935 V	3.932 V	3.932 V	3.933 V	3.933 V	3.935 V	3.935 V	3.933 V
		3.933 V	3.934 V	3.934 V	3.934 V				
M8 (#85- #96)	47.2 V	3.932 V	3.935 V	3.934 V	3.933 V	3.933 V	3.936 V	3.933 V	3.933 V
		3.934 V	3.933 V	3.933 V	3.934 V				

M9 (#97- #108)	47.2 V	3.934 V	3.933 V	3.934 V	3.933 V	3.933 V	3.933 V	3.934 V	3.932 V
		3.933 V	3.934 V	3.935 V	3.934 V				

Module Temperature Information										
Max Temperature:				10.9 °C		Min Temperature:			10.1 °C	
Average Temperature:				10.4 °C						
				Low			High		Warning	Not OK
	1	2	3	4	5	6	7	8		
M1 (T1-T2)	10.5 °C	10.4 °C								
M2 (T3-T4)	10.9 °C	10.9 °C								
M3 (T5-T6)	10.4 °C	10.3 °C								
M4 (T7-T8)	10.5 °C	10.5 °C								
M5 (T9-T10)	10.5 °C	10.3 °C								
M6 (T11-T12)	10.3 °C	10.4 °C								
M7 (T13-T14)	10.1 °C	10.1 °C								
M8 (T15-T16)	10.5 °C	10.4 °C								
M9 (T17-T18)	10.1 °C	10.1 °C								